




Harold's Physics Formulas – Algebra

Cheat Sheet

30 October 2026

	Mechanics: Linear Translation	Mechanics: Angular / Rotational	Electricity / Magnetism	Fluid Mechanics / Thermodynamics	Atomic and Nuclear / Waves and Optics
Kinematics	Bold = Vector Red = Memorize	See Harold's Physics Units of Measure Cheat Sheet See Harold's Physics of Projectiles Cheat Sheet		See Harold's Physics Optics Cheat Sheet See Math and Greek Symbols	
Position (m) (rad)	<p><i>Horizontal:</i></p> $x = x_0 + v_{0x}t + \frac{1}{2}a_x t^2$ <p>(constant a_x)</p> <p><i>Vertical:</i></p> $y = y_0 + v_{0y}t - \frac{1}{2}gt^2$ <p>(up is +, constant g, neglect air resistance)</p> $\Delta x = x_f - x_0$ $x = x_0 + vt$ <p>(constant v)</p>	<p><i>Circular:</i></p> $\theta = \theta_0 + \omega_0 t + \frac{1}{2}\alpha t^2$ <p>(constant α)</p> $\Delta \theta = \theta_f - \theta_0$ $\theta = \theta_0 + \omega t$ <p>(constant ω)</p>	$10^{-30} = \text{quetto-}$ $10^{-27} = \text{ronto-}$ $10^{-24} = \text{yocto-}$ $10^{-21} = \text{zepto-}$ $10^{-18} = \text{atto-}$ $10^{-15} = \text{femto-}$ $10^{-12} = \text{pico-}$ $10^{-9} = \text{nano-}$ $10^{-6} = \text{micro-}$ $10^{-3} = \text{milli-}$ $10^{-2} = \text{centi-}$ $10^{-1} = \text{deci-}$ $10^0 = 1$ $10^1 = \text{deca-}$ $10^2 = \text{hecto-}$ $10^3 = \text{kilo-}$ $10^6 = \text{mega-}$ $10^9 = \text{giga-}$ $10^{12} = \text{tera-}$ $10^{15} = \text{peta-}$ $10^{18} = \text{exa-}$ $10^{21} = \text{zetta-}$ $10^{24} = \text{yotta-}$ $10^{27} = \text{ronna-}$ $10^{30} = \text{quetta-}$	<p><u>Fluid Mechanics:</u></p> <p>Mass Density:</p> $\rho = \frac{m}{V}$ $\Delta \ell = \alpha \ell_0 \Delta T$	<p><u>Optics:</u></p> $f = \frac{v}{\lambda}$ $\frac{1}{d_o} + \frac{1}{d_i} = \frac{1}{f}$ <p>Refraction (bend):</p> $n = \frac{c}{v}$ <p>Snell's Law:</p> $n_1 \sin \theta_1 = n_2 \sin \theta_2$ <p>(angles measured from the normal)</p> $\frac{n_1}{n_2} = \frac{v_2}{v_1}$
	$s = r\theta$				
	$x(t) = A \cos(\omega t + \phi)$ $x(t) = A \cos(2\pi f t + \phi)$ <p><u>Waves:</u></p> $f(x, t) = A \sin\left(2\pi\left(ft - \frac{x}{\lambda}\right) + \phi\right) + k$			<p><u>Optics:</u></p> 	<p>Diffraction (spread):</p> $\Delta L = d \sin \theta$ <p>Double-slit Maxima:</p> $d \sin \theta = m\lambda$ $m = 0, \pm 1, \pm 2, \dots$

	Mechanics: Linear Translation	Mechanics: Angular / Rotational	Electricity / Magnetism	Fluid Mechanics / Thermodynamics	Atomic and Nuclear / Waves and Optics
Velocity (m/s) Angular Velocity / Angular Frequency (rad/s)	$v_{ave} = \frac{\Delta x}{\Delta t}$ $\Delta v = v_f - v_0$ <p>Constant linear acceleration:</p> $v = v_0 + at$ $v^2 = v_0^2 + 2a\Delta x$ $\bar{v} = \frac{v_0 + v}{2}$	$\omega_{ave} = \frac{\Delta \theta}{\Delta t}$ $\Delta \omega = \omega_f - \omega_0$ <p>Constant angular acceleration:</p> $\omega = \omega_0 + \alpha t$ $\omega^2 = \omega_0^2 + 2\alpha\Delta\theta$ $\bar{\omega} = \frac{\omega_0 + \omega}{2}$ $\omega = \frac{2\pi}{T} = 2\pi f$ $\omega_{spring} = \sqrt{\frac{k}{m}}$ $\omega_{pendulum} = \sqrt{\frac{g}{\ell}}$ <p>(for small $\Delta\theta$)</p>	<p>Speed of Light:</p> $c \approx 3.00 \times 10^8 \frac{m}{s}$	<p><u>Fluid Mechanics:</u></p> <p>Continuity:</p> $A_1 v_1 = A_2 v_2$ <p>(Steady incompressible flow)</p> <p>Torricelli's Law:</p> $v = \sqrt{2gh}$ <p>(Speed of fluid exiting a small outlet in a large tank, equal pressure at the surface and outlet, negligible losses.)</p>	<p><u>Waves and Optics:</u></p> $v = f\lambda$ <p>Reflection: (return into the original medium)</p> <p>Critical angle:</p> $\sin \theta_c = \frac{n_2}{n_1}$ <p>For light traveling from medium 1 to medium 2, with $n_1 > n_2$.</p> <p>Maxima for a thin film:</p> <p>Constructive</p> $2d = \frac{\lambda}{2n}, 3\frac{\lambda}{2n}, 5\frac{\lambda}{2n} \dots$ $= \left(m + \frac{1}{2}\right) \frac{\lambda}{n}$ <p>(λ = vacuum wavelen.)</p> <p>Destructive</p> $2d = \frac{m}{n} \lambda$ <p>(Assumes normal incidence and one reflection phase reversal)</p>
	$v = \omega r$ $v(t) = -A\omega \sin(\omega t + \phi)$ $v(t) = -A(2\pi f) \sin(2\pi f t + \phi)$		 <p>The diagram shows a circle of radius r rotating counter-clockwise with angular velocity ω. A point on the circumference moves with linear velocity v. The arc length traveled is s, and the angle in radians is θ. The relationship $\theta = \frac{s}{r}$ is shown. Below the circle, the formulas $\omega = \frac{v}{r}$ and $\omega = 2\pi f$ are given, with a note that f is frequency in revolutions/s.</p>		





	Mechanics: Linear Translation	Mechanics: Angular / Rotational	Electricity / Magnetism	Fluid Mechanics / Thermodynamics	Atomic and Nuclear / Waves and Optics
Acceleration (m/s ²) (rad/s ²)	<u>Linear:</u> $a_{ave} = \frac{\Delta v}{\Delta t}$ $a = \frac{\sum F}{m} = \frac{F_{net}}{m}$ <u>Straight-line motion:</u> $\mathbf{a} = \mathbf{a}_t$ (a has no normal acceleration component)	<u>Angular:</u> $\alpha_{ave} = \frac{\Delta \omega}{\Delta t}$ $\alpha = \frac{\sum \tau}{I} = \frac{\tau_{net}}{I}$ <u>Centripetal (center):</u> $a_c = \frac{v^2}{r} = \omega^2 r$	Physical Constants (2022 CODATA): Gravitational Constant $G \approx 6.6743 \times 10^{-11} \frac{m^3}{kg \ s^2}$ Std. Acceleration Gravity $g_n \approx 9.81 \frac{m}{s^2} \approx 32.1740 \frac{ft}{s^2}$, ($g \approx g_n$) Speed of Light in Vacuum $c \approx 3.00 \times 10^8 \frac{m}{s}$ Electron-Volt $1eV \approx 1.6022 \times 10^{-19} J$ Elementary Charge $e \approx 1.6022 \times 10^{-19} C$, ($q_e = -e$) Mass of an Electron $m_e \approx 9.1094 \times 10^{-31} kg$ Mass of a Proton $m_p \approx 1.6726 \times 10^{-27} kg$ Mass of a Neutron $m_n \approx 1.6749 \times 10^{-27} kg$ Electric Permittivity $\epsilon_0 = \frac{1}{\mu_0 c^2} \approx 8.8542 \times 10^{-12} \frac{C^2}{Nm^2}$ Magnetic Permeability $\mu_0 \approx 1.2566 \times 10^{-6} \frac{N}{A^2}$ Boltzmann Constant $k_B \approx 1.3806 \times 10^{-23} \frac{J}{K}$ Coulomb Constant $k_e = \frac{1}{4\pi\epsilon_0} \approx 8.9876 \times 10^9 \frac{Nm^2}{C^2}$ Faraday Constant $F \approx eN_A \approx 9.6485 \times 10^4 \frac{C}{mol}$ Planck Constant $h \approx 6.6261 \times 10^{-34} Js$ Avogadro Constant $N_A \approx 6.0221 \times 10^{23} / mole$ Ideal Gas Constant $R \approx 0.08206 \frac{L \ atm}{mole \ K}$ " $R \approx 8.3145 \frac{J}{mole \ K}$ pi $\pi \approx 3.1416$		
					
	$a^2 = a_t^2 + a_r^2$				
	$a_r = -a_c$ radial/centripetal (outward radial is +) $a_t = a_\theta$ tangential/transverse				
	$a_t = \alpha r$ (fixed-radius circular motion) $a(t) = -A\omega^2 \cos(\omega t + \phi)$				

	Mechanics: Linear Translation	Mechanics: Angular / Rotational	Electricity / Magnetism	Fluid Mechanics / Thermodynamics	Atomic and Nuclear / Waves and Optics
Dynamics	See Harold's Physics Forces with FBD Cheat Sheet See Harold's Physics Atwood Machine Cheat Sheet		See Harold's Physics Forces on an Incline Cheat Sheet See Harold's Physics Forces on an Incline with Pulley Cheat Sheet		
Mass (kg) / Moment of Inertia (kg • m ²)	m = actual mass I = rotational analog of mass Inertia is an object's resistance to changes in its state of motion.	$I = \sum mr^2$ (r = perp. distance from the rotation axis.)	$m_p \approx m_n$ $m_p \approx 1,836 m_e$	Density: $\rho = \frac{m}{V}$ $\rho_{H_2O} = 1000 \frac{kg}{m^3}$	Magnification: $ M = \left \frac{d_i}{d_o} \right = \left \frac{h_i}{h_o} \right $ $M_{Telescope} = -\frac{f_{objective\ lens}}{f_{eyepiece}}$
Momentum (kg•m/s) (kg • m ² /s)	Constant Mass: $\mathbf{p} = m\mathbf{v}$ $p = m\omega r$ Constant m : $\Delta \mathbf{p} = m\Delta \mathbf{v}$ $\Delta \mathbf{p} = m\mathbf{v}_2 - m\mathbf{v}_1$	Constant Mass: $L = pr \sin \theta$ $L = mvr \sin \theta$ Fixed-axis constant I : $\Delta L = I\Delta \omega$ $\Delta L = I\omega_2 - I\omega_1$		Fluid Mechanics: $\Delta P = \rho g \Delta h$ (Δh is the increase in depth) $F = \rho V g$	Atomic and Nuclear: $\lambda = \frac{h}{p}$
	Conservation of Linear Momentum: $\mathbf{p}_i = \mathbf{p}_f$ $\sum m\mathbf{v}_i = \sum m\mathbf{v}_f$	Conservation of Angular Momentum: $L_i = L_f$ $\sum I\omega_i = \sum I\omega_f$	<div><div><div>Elastic Collision</div><div>Kinetic energy and momentum are conserved</div><div><div>Before Collision</div><div>During Collision</div><div>After Collision</div></div></div><div>vs.</div><div><div>Inelastic Collision</div><div>Kinetic energy is not conserved, but momentum is conserved</div><div><div>Before Collision</div><div>During Collision</div><div>After Collision</div></div></div></div>		
	Elastic Collision: $m_A(v_A)_1 + m_B(v_B)_1 = m_A(v_A)_2 + m_B(v_B)_2$ (conservation of momentum) $K_{A1} + K_{B1} = K_{A2} + K_{B2}$ (conservation of kinetic energy)	Perfectly Inelastic Collision: $m_A(v_A)_1 + m_B(v_B)_1 = (m_A + m_B)v_2$ (conservation of momentum)			







	Mechanics: Linear Translation	Mechanics: Angular / Rotational	Electricity / Magnetism	Fluid Mechanics / Thermodynamics	Atomic and Nuclear / Waves and Optics
Force (N = kg•m/s²) / Torque (N•m)	$F = ma$ $F_g = mg$ <i>(constant mass)</i> $\sum \mathbf{F} = \mathbf{F}_{net} = m\mathbf{a}$ $F_{net,ave} = \frac{\Delta p}{\Delta t}$ Friction: $F_{\mu_s} \leq \mu_s N$ $F_{\mu_k} = \mu_k N$ <i>Typically $0 \leq \mu_k \leq \mu_s$</i> Gravitational Force: $F_G = G \frac{m_1 m_2}{r^2}$ Hooke's Law: $\mathbf{F}_s = -k\Delta\mathbf{x}$	$\tau = I\alpha$ (fixed-axis rotation with constant I) $\tau = rF \sin \theta = rF_{\perp}$ $\sum \boldsymbol{\tau} = \boldsymbol{\tau}_{net} = I\boldsymbol{\alpha}$ $\tau_{net,ave} = \frac{\Delta L}{\Delta t}$ $F = ma_c$ $F = \frac{mv^2}{r} = mr\omega^2$ <i>(net inward force)</i>	<u>Electricity:</u> Coulomb's Law: $F = k \frac{ q_1 q_2 }{r^2}$ $F = \frac{1}{4\pi\epsilon_0} \frac{ q_1 q_2 }{r^2}$ $\mathbf{F} = Eq$ <u>Magnetism:</u> $F_B = qvB \sin \theta $ $F_B = BI\ell \sin \theta$	<u>Fluid Mechanics:</u> $P = \frac{F}{A}$ $\Delta P = \rho hg$ $F_{buoy} = \rho Vg$ Universal Gas Law: $PV = nRT = Nk_B T$ <i>(absolute pressure; T is in kelvins)</i>	
Impulse (N•s) (N•m•s)	Constant net force: $\mathbf{J} = \mathbf{F}\Delta t$ $\mathbf{J} = \Delta\mathbf{p} = m\Delta\mathbf{v}$	Constant net torque: $H = \Delta L = \tau\Delta t$ $H = I\Delta\omega$			

	Mechanics: Linear Translation	Mechanics: Angular / Rotational	Electricity / Magnetism	Fluid Mechanics / Thermodynamics	Atomic and Nuclear / Waves and Optics
Energy					
Work (J = N•m)	Constant force: $W = F_{\parallel}s = Fs \cos \theta$ (s is displacement)	Constant torque: $W = \tau \Delta \theta$ (fixed axis, θ in rad)	$W = QV_{\text{drop}}$ $W_{\text{electric}} = -q\Delta V$	<u>Thermodynamics:</u> $W = P\Delta V$ (constant pressure) $e = \left \frac{W}{Q_H} \right = \left \frac{\text{output/cycle}}{\text{heat absorbed}} \right $ Max. Carnot efficiency ² : $e_c = \frac{T_H - T_C}{T_H}$	¹ Needs steady, incompressible, inviscid flow along a streamline, with no pump/turbine work. ² T_H, T_C in kelvins
Kinetic Energy (J)	Translational: $K_{\text{trans}} = \frac{1}{2}mv^2$	Rotational: $K_{\text{rotat}} = \frac{1}{2}I\omega^2$	1 eV $\approx 1.60 \times 10^{-19} \text{ J}$	<u>Fluid Mechanics:</u> Bernoulli's Equation ¹ : $P_1 + \rho gy_1 + \frac{1}{2}\rho v_1^2 = P_2 + \rho gy_2 + \frac{1}{2}\rho v_2^2$	
	<u>Work-Energy Theorem:</u> $W_{\text{net}} = \Delta K$ $W_{\text{net}} = W_{\text{other}} - \Delta U = W_{\text{other}} - \Delta U_g - \Delta U_s$ $\Delta K = K_2 - K_1 = \frac{1}{2}m(v_2^2 - v_1^2) + \frac{1}{2}I(\omega_2^2 - \omega_1^2)$		<u>Mechanical Energy:</u> $E_{\text{mech}} = K + U$ $K = K_{\text{trans}} + K_{\text{rotat}}$ $U = U_g + U_s$		<u>Thermodynamics:</u> $K_{\text{avg}} = \frac{3}{2}k_B T$ (T is in kelvins)
Potential Energy (J)	Surface of Earth Gravity: $\Delta U_g = mg\Delta h$ $U_g = mgh$ Planetary Gravity: $U_G = -G \frac{m_1 m_2}{r}$	Coiled Spring: $U_s = \frac{1}{2}k\Delta x^2$	Point charges: $U_E = qV$ $U_E = \frac{1}{4\pi\epsilon_0} \frac{q_1 q_2}{r}$	<u>Fluid Mechanics:</u> $P = P_0 + \rho gh$ Continuity of Mass: $\rho_1 A_1 v_1 = \rho_2 A_2 v_2$	<u>Atomic and Nuclear:</u> $E = hf$ $E_0 = mc^2$ $\Delta E = (\Delta m)c^2$
	<u>Conservation of Mechanical Energy:</u> $\Delta E_{\text{mech}} =$ $\Delta(K + U_g + U_s) = 0$ (if only conservative forces do work)	<u>Nonconservative Work:</u> $W_{\text{noncons.}} =$ $\Delta(K + U_g + U_s)$	Capacitor/inductor: $U_C = \frac{1}{2}QV = \frac{1}{2}CV^2$ $U_L = \frac{1}{2}LI^2$	Continuity of Volume: $A_1 v_1 = A_2 v_2$ <u>Thermodynamics 1st Law³:</u> $\Delta U_{\text{internal}} = Q - W_{\text{by}}$	³ Closed system; negligible changes in macroscopic kinetic and potential energy.

	Mechanics: Linear Translation	Mechanics: Angular / Rotational	Electricity / Magnetism	Fluid Mechanics / Thermodynamics	Atomic and Nuclear / Waves and Optics
Heat Energy (J)	Energy transferred by heating is Q . Closed-system energy balance: $Q > 0$ into the system $W_{by} > 0$ for work done by it			<u>Thermodynamics:</u> $H = \frac{Q}{\Delta t} = \frac{kA\Delta T}{L}$ (steady heat conduction) $Q = mL_f$ $Q = mL_v$	Hydrogen Electron Energy Levels: $E_n = \frac{-13.6 \text{ eV}}{n^2}$ $n = \text{principal quantum number (1, 2, 3, etc.)}$
Energy (J)	Conservation of Energy for an isolated system: $E_{total} = E_i = E_f$ $E_{total} = \sum E_i = \sum E_f$ $E_{total} = K + U_{potential} + U_{internal}$ Closed-system energy balance: $\Delta E_{total} = \Delta K + \Delta U_{potential} + \Delta U_{internal} = Q - W_{by}$			$\Delta E = Q = mc\Delta T = mc(T_f - T_i)$ (Heat is the only energy transfer, no phase change, and approximately constant specific heat) $T_f = \frac{m_1c_1T_{1i} + m_2c_2T_{2i}}{m_1c_1 + m_2c_2}$ (No heat exchange with surroundings, no phase change, negligible calorimeter heat capacity, constant specific heats) $c_{H_2O} = 4,184 \frac{J}{kg \cdot K}$	
Power (W)	Energy transferred by the process: $P_{ave} = \frac{W}{\Delta t} = \frac{\Delta E_{transferred}}{\Delta t}$		$P = IV$ $P = I^2R$ $P = \frac{V^2}{R}$	$P = \Delta p Q$ where: $p = \text{pressure} \left(\frac{N}{m^2} \right)$ $Q = \text{volumetric flow rate} \left(\frac{m^3}{s} \right)$	
	$P = F_{\parallel} v$ $P = Fv \cos \theta$	$P = \tau_{\parallel} \omega$ $P = \tau \omega \cos \phi$			

	Mechanics: Linear Translation	Mechanics: Angular / Rotational	Electricity / Magnetism	Fluid Mechanics / Thermodynamics	Atomic and Nuclear / Waves and Optics
Engineering Application	See Harold's Center of Mass / Moment of Inertia Cheat Sheet See Harold's Physics Doppler Effect Cheat Sheet				
Period (s) / Frequency (Hz)	$T = \frac{1}{f}$ $f = \frac{1}{T}$ <p>Kepler's Third Law: $T^2 = \left(\frac{4\pi^2}{GM}\right)r^3$ <i>(M dominant; r is circular-orbit radius)</i></p>	$T = \frac{1}{f} = \frac{2\pi}{\omega} = \frac{2\pi r}{v}$ $T_{spring} = 2\pi\sqrt{\frac{m}{k}}$ $T_{pendulum} = 2\pi\sqrt{\frac{\ell}{g}}$ <i>(small oscillations)</i>	$T_{angular} = \frac{2\pi}{ b }$ <p>For: $y = \sin(b\theta)$ $y = \cos(b\theta)$</p>	 <p>Waves and Optics: $f = \frac{v}{\lambda}$</p> <p>Doppler Effect: $f_r = f_s \left(\frac{v \pm v_r}{v \mp v_s} \right)^*$</p> <p><i>* = Receiver toward source: numerator +; source toward receiver: denominator -, with speeds measured relative to the medium.</i></p>	
Center of Mass (m)	$x_{CM} = \frac{m_1x_1 + m_2x_2}{m_1 + m_2}$ $r_{CM} = \frac{\sum mr}{\sum m}$		<div> $x_{CM} = \frac{\sum m_i x_i}{\sum m_i}$ $y_{CM} = \frac{\sum m_i y_i}{\sum m_i}$ </div> 		
Rigid Bodies (Statics)	$\sum F_x = 0$ <i>(Right = '+')</i> $\sum F_y = 0$ <i>(Down = '-')</i>	$\sum \tau = 0$ <i>(CW = '-')</i>			

	Mechanics: Linear Translation	Mechanics: Angular / Rotational	Electricity / Magnetism	Fluid Mechanics / Thermodynamics	Atomic and Nuclear / Waves and Optics
Conservation Laws					
Fundamental Principle	Conservation of Linear Momentum	Conservation of Angular Momentum	Conservation of Electric Charge	Conservation of Mass (or Matter)	Conservation of Energy
Discipline	Physics	Physics	Chemistry & Circuits	Chemistry & Fluid Mechanics	Physics
Formula	$\sum \mathbf{p}_i = \sum \mathbf{p}_f$ $\sum m\mathbf{v}_i = \sum m\mathbf{v}_f$	$\sum \mathbf{L}_i = \sum \mathbf{L}_f$ $\sum I\boldsymbol{\omega}_i = \sum I\boldsymbol{\omega}_f$	$\sum Q_i = \sum Q_f$	$\sum m_i = \sum m_f$	$\sum E_i = \sum E_f$
Example	Zero net external impulse for linear momentum. Zero net external angular impulse about the chosen origin for angular momentum.		Kirchhoff's Current Law (KCL): $\sum_{i=1}^n I_i = 0$	Continuity of Mass: $\rho_1 A_1 v_1 = \rho_2 A_2 v_2$ (Classical mass conservation, since mass alone is not conserved in nuclear reactions.)	$\sum E_i = \text{constant}$ $\Delta E_{\text{total}} = \Delta K + \Delta U_{\text{potential}} + \Delta U_{\text{internal}} = Q - W_{\text{by}}$
					For an isolated system: $E_{\text{total}} = K + U_{\text{potential}} + U_{\text{internal}} = \text{constant}$

Electricity			
Terms	Formulas	See Harold's Electromagnetic Spectrum Cheat Sheet See Harold's DC Circuits Cheat Sheet	
Electric Field (V/m or N/C)	$\mathbf{E} = \frac{\mathbf{F}}{q}$ $E_{x,avg} = -\frac{\Delta V}{\Delta x}$ $E = \rho J$ <p>(ρ = electrical resistivity)</p>	$E_{r,avg} = -\frac{\Delta V}{\Delta r}$	<p>Gauss's Law:</p> $\phi = \frac{Q_{enc}}{\epsilon_0}$
Potential / Voltage (V)	$V = IR$ $V = \frac{Q}{C}$	$V = k \sum_i \frac{q_i}{r_i}$ $V = \frac{1}{4\pi\epsilon_0} \sum_i \frac{q_i}{r_i}$	
Current (A)	$I_{ave} = \frac{\Delta Q}{\Delta t}$ $I = \frac{V}{R}$	$I = n e v_d A$	
Circuits		Series	Parallel
Circuit Terms	 Resistor  Capacitor  Inductor		
Resistance (Ω)	$R = \frac{V}{I}$ $R = \frac{\rho \ell}{A}$	$R_s = \sum_i R_i$	$\frac{1}{R_p} = \sum_i \frac{1}{R_i}$ $R_p = \frac{R_1 R_2}{R_1 + R_2}$
Inductance (H)	$L = N \frac{\Phi}{I}$ $L = \mu_0 \frac{N^2 A}{\ell}$	$L_s = \sum_i L_i$ <p>L_s and L_p assume negligible mutual inductance. ¹ For a long air-core solenoid; negligible end effects.</p>	$\frac{1}{L_p} = \sum_i \frac{1}{L_i}$
Capacitance (F)	$C = \frac{Q}{V}$ $C = \frac{\kappa \epsilon_0 A}{d}$	$\frac{1}{C_s} = \sum_i \frac{1}{C_i}$	$C_p = \sum_i C_i$
Kirchhoff's Current Law (KCL)	$\sum_{i=1}^n I_i = 0$ <p>The algebraic sum of currents in a network of conductors meeting at a point (node) is zero.</p>		
Kirchhoff's Voltage Law (KVL)	$\sum_{i=1}^n V_i = 0$ <p>The directed sum of the potential differences (voltages) around any closed loop is zero.</p>	 <p>KVL: $-v + v_1 + v_2 = 0$</p>	

Magnetism	
Term	Formulas
Magnetic Field (T)	$B = \frac{\mu_0}{2\pi} \frac{I}{r}$ <p>(Long straight wire)</p> <p>Solenoid: $B_s = \mu_0 n I$ <p>(Long air-core solenoid, away from the ends)</p> <p>where $n = \frac{N}{\ell}$ turns per meter</p> <p>Moving-charge magnetic field: $B = \frac{\mu_0 q v r}{4\pi r^3} \sin \theta$ <p>(Nonrelativistic approximation, $v \ll c$)</p></p></p>
Magnetic Flux (Wb)	$\phi_B = BA \cos \theta$ <p>(Uniform field through a flat surface; θ is measured from the surface normal)</p>
EMF (V)	$\varepsilon = Blv$ <p>(magnitude; perpendicular rod, velocity, and uniform magnetic field)</p> $\varepsilon_{avg} = - \frac{N \Delta \phi_B}{\Delta t}$ <p>(N turns, stationary loop)</p>

Sources

- [NIST SP 961](https://physics.nist.gov/cuu/pdf/wall_2022.pdf) (2022). CODATA Recommended Values of the Fundamental Physical Constants: 2022.
- Wikipedia (2025).
 - Metric prefix. https://en.wikipedia.org/wiki/Metric_prefix
 - SI derived unit. https://en.wikipedia.org/wiki/SI_derived_unit

Acknowledgements

- Proofread with assistance from ChatGPT 6.1 Sol, <https://chatgpt.com/>